

Extend the Life of Your Water Heater and Protect Your Investment without Salt or Maintenance!

NO SALT NO CHEMICALS NO MAINTENANCE NO DRAIN NO ELECTRICITY



NaturalSof Hot uses our proven catalytic technology to protect a single residential tanked or tankless water heater from hard water limescale.

NaturalSof Hot prevents limescale build up in new and old water heaters while gradually removing current limescale deposition. The system is completely maintenance free. *

NaturalSof Hot requires no chemicals, electricity or salt.

As the NaturalSof replaces existing water softeners all the running costs and inconveniences associated with the use of conventional water softeners is eliminated. No more salt carrying, water waste and no more damage to the environment.

Periodic draining/flushing of your water heater is still recommended.

NaturalSof Hot is perfect for treating the water supply to an RV.

Height (in)	12.25
Connection	¾" NPT
Min Flow Required (gpm)	0.5
Max Flow @ 50 psi (gpm)*	5.0
Cartridge Diameter/Height (in)	2.5/10
Clearance needed below (in)	6

Installation Guidance: NaturalSof Hot should be installed on the feed line to the water heater preferably 3 or more feet of waterline from the heater. The unit should be oriented as pictured above so that the water lines enter and exit the unit horizontally. A NaturalSof (NS05) MUST be installed on any hot water recirculation return line to the heater.

* A standard 2.5" x 10" sediment or carbon filter may be inserted inside the canister as an option to improve water quality. The optional filter would be changed every 6 months and is not related to scale prevention. Type of filter cartridge may affect Max Flow.